



LEVASSEUR
Your paint expert

IMPREGNATION AG VARNISH AGUA

PRODUCT DESCRIPTION

The Impregnation Varnish is composed of an acrylic resin in emulsion in water. It can be used as primer on any mineral support before Anti-Graffiti treatment (bluestone, brick, concrete, natural stone).

PRODUCT REFERENCE

84/786

APPLICATION FIELD

This product has 2 functions in the Anti-Graffiti system :

- It fills the pores of the support.
- This primer prevents any undesirable change of color through the application of Polyfond Anti-Graffiti Varnish. Without that, a support like bluestone, for example, it gets wet in contact with the varnish and would lose its natural aspect.

In the case of medium-porous system, 2 layers of this varnish are necessary for obtaining a closed-pore system.

APPLICATION

Ready to use. Brush or spray gun.

Verification before the application of the finishing coat : Trickle a little water down the length of the treated support. Where water is absorbed, it dampens the medium and changes its color, it will be necessary to apply an additional coat of the varnish. This test should be carried out 24h following application.

COVERABILITY

Coverability : 10 m² / L, depending on the porosity and the support's irregularity.

Drying time between 2 layers : 6 hours at 20°C. % dry substance : 17%.

CLEANING OF THE MATERIAL

With water.

STORAGE CONDITIONS

Conservation: 1 year in a tightly closed container and refrigerated.

Not resistant to frost, do not transport or store below 5°C.

Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - info@g-levasseur.com - www.levasseur.be