



AGUALAC PU

MATT – SATIN - GLOSS

PRODUCT DESCRIPTION

AGUALAC PU is a very high quality enamel paint based on a water-based acryl-polyurethane dispersion. It has excellent covering power and a beautifully rounded surface. Perfect brushability.
Matt, satin or gloss finish. Available in white and a choice of other colours.

FIELD OF APPLICATION

AGUALAC PU can be applied indoors and outdoors (under cover) to all types of surface: metal, wood, plaster, cement, MDF, metal, wood, plaster, cement, MDF. Substrates previously prepared with a suitable primer (Flexaprim Agua, Hydrogrip, etc).

CONDITIONS OF USE

Ambient temperature: min +5 to +30°C during application
Substrate temperature: min. +5°C
Relative humidity: max. 70%

MIX PREPARATION AND APPLICATION

The product can be applied with a brush, roller or spray gun in 2 coats.

- If using a brush or roller, thin with 2% water.
- For airless spraying, do not thin.
- For HVLP spraying, dilute with 5% water..

CLEANING EQUIPMENT

With Water.

CHARACTERISTICS

Shine: Satin 30GU to ISO2813, Rhopoint 60° (may vary according to shade)
Shine: Matt 10GU to ISO2813, Rhopoint 60° (may vary with shade)
Shine: Gloss 65GU to ISO2813, Rhopoint 60° (may vary according to shade)
Density: 1.2 kg/L (depending on shade)
Hardness: 88s (after 24h) and 111s (after 1 week)
Dry extract by volume: 36
Dry extract by weight: 46
Fineness: <10µm (according to ISO1524)
Washability: Class I (as per ISO11998)
Recoatable: 4 hours (HR<70% and 20°C)
Coverage: 8 to 10 m²/ltr (depending on substrate porosity)
Drying time: 1 hr HP, 2 hrs through-dry
Viscosity: 3000 cp (Haake, rotor n°1 20°C)
VOC: 12 g/L (category A/i limit 140g/L 2010)



LEVASSEUR
Your paint expert

09-07-21 / V1

STORAGE CONDITIONS

1 year in unopened and unopened original packaging in a well-ventilated, dry place, away from light.

Our product information and technical recommendations are intended to help professional workers. We always recommend carrying out a trial application first.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - info@g-levasseur.com - www.levasseur.be