



**LEVASSEUR**  
*Your paint expert*

# FLEXAPRIM AGUA

## PRODUCT DESCRIPTION

Base colour matt for internal use. Flexaprim Agua is applied as universal base colour (and top coat) on wood, gypsum, plaster, cement, cement asbestos, MDF (Main Distribution Frame), particle board, Alkyd colour. Flexaprim agua isolates tannic acid and nicotine.

## COMPOSITION

Acrylic resin 100% water.

## APPLICATION

To apply with brush or roll.  
1<sup>st</sup> layer : Dilute with 5 % of water.  
2<sup>nd</sup> layer : Dilute with 3-4 % of water.

## CLEANING

With water.

## PROPERTIES

Density: 1,47.  
Color : White.  
Dry Matter: 60 %.  
Performance : 8 to 10 m<sup>2</sup>/ltr.  
Drying : Flewaprim Agua can be recovered after 4 hours.  
VOC : Flexaprim Agua contains 2g/l VOC.

## STORAGE CONDITIONS

Does not stand frost.

*Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.*

---

### S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL  
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - [info@g-levasseur.com](mailto:info@g-levasseur.com) - [www.levasseur.be](http://www.levasseur.be)