



LEVASSEUR
Your paint expert

FLEXAPRIM SOLVENT

PRODUCT DESCRIPTION

Flexaprim can be used as a top coat or as a universal mat primer on all types of substrate like: Wood, metal, plaster, cement, eternit, panels...

It dries quickly and provides a good flow during the application.

Flexaprim has an excellent covering power.

Flexaprim is of a thixotropic consistency.

COMPOSITION

Alkyd binder based paint

USE

Application with brush, roller or spray gun.

Flexaprim is ready to use but it can be diluted up till 5 and 10% with Thinner Flexaprim for the first layer and with 2 till 5% for the second layer

CLEANING AND DILUTION

With Thinner Flexaprim.

MECHANICAL PROPERTIES

Colour : White, can be tinted with universal pigments.

Coverage : 8-10 m²/L.

Drying : 4 to 6 hours.

Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.

S.A. LEVASSEUR NEWCO N.V.

Rue du Bourdon - 121 - Horzelstraat - B - 1180 BRUXELLES - BRUSSEL
Tel. 02/ 376 00 18 - Fax. 02/ 376 38 86 - info@g-levasseur.com - www.levasseur.be