



# TOPTEx EXTERIEUR

## PRODUCT DESCRIPTION

Exterior paint based on an unsaponifiable acrylic copolymer dispersion.

TOPTEx EXTERIEUR has optimum water vapour permeability and very good resistance to water and dirt when applied to exterior walls and facades. A washable, water-thinnable paint that can also be applied indoors.

TOPTEx EXTERIEUR adheres perfectly to any clean surface and has excellent coverage.

Finish: Matt. Available in all colours

## USE OF THE PRODUCT

For application on new or chalky facades and walls, we recommend prior application of Hydrofix primer. An opacifying primer such as Flexaprim is also suitable.

TOPTEx EXTERIEUR is best applied in two successive coats.

Drying time between 2 coats: 4-6 hours.

Apply the first coat diluted with 5-10% water.

Apply the second coat diluted with a maximum of 5% water.

Application can be made with a brush, roller or spray gun. In the latter case, dilute with up to 20% water.

## DRYING TIME AT 60% RH AND 20°C

Touch dry : 1 hour

Re-coatable : 4 to 6 hours

## CARACTERISTICS

Coverage :	± 8-10 m <sup>2</sup> /L	Viscosity :	6000 CP (Brookfield r5, 50rpm)
Dry Extract:	31% by volume and 64% by weight	Density :	1,5 KG/L
Washability:	Class 1 to ISO 11998	Opacity :	Class 2 to ISO 6504-3. Application at 200µ wet

## CLEANING OF THE MATERIAL

Immediately with water

## STORAGE CONDITIONS

1 year in the original closed and unopened packaging. Store in a well ventilated area at a room temperature between +5 and +30°C.

*Our information on the technical product is used only as assistance to professional workers. During the implementation of our products, we always advise to start with a test on a small area.*